

ImagePerfect™ 2907 Static Cling Film is a reusable product that has been formulated to adhere to smooth, glossy surfaces without the need of an adhesive system. It has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

IP 2907

ImagePerfect™ 2907 sticks/clings to smooth, glossy surfaces such as glass, ceramic tiles, smooth plastics (such as acrylic) and glossy metal surfaces without an adhesive system and can be removed without leaving any residue behind. As a reusable product, it is an effective solution for multi-use decorative and informative graphics in retail locations, offices, educational establishments, trade shows, etc. We would not recommend contour cutting of the graphics within the first 72 hours after printing. Please note that the printed graphic should not be applied with the ink in direct contact with glass, as this could cause some ink transfer onto the glass.

| Specifications | |
|------------------------|--|
| DESCRIPTION | Static cling film |
| COLOUR | White |
| THICKNESS | 180μ |
| WEIGHT | N/A |
| TEMPERATURE RANGE | -30°C to +70°C |
| DURABILITY (UNPRINTED) | N/A |
| FLAME RETARDANCY | N/A |
| SHELF LIFE | 6 months, 20°C / 50% humidity |
| RECOMMENDATION | For optimum quality, please ensure that the media feed adjustment has been completed for this material |

© September 2015 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific features of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.